



**FP7700 Series locking-type photoelectric control**

The FP7700 Series locking-type photoelectric controls are designed to meet stringent electric utility requirements for roadway lighting.

These photoelectric controls have provided more hours of dependable operation than any other photocontrol. Conservatively rated for 5,000 operations (13 years) on loads of 1800VA, the FP7700 Series is the industry standard.

The FP7700 Series is a highly reliable control. A wide, crosslinked polyethylene gasket assures weatherproof sealing with the luminaire socket.

**Application**

Series FP7700 state-of-the-art, controls are designed for industrial, commercial, street and highway luminaires equipped with locking-type receptacles. The control's "easy-to-test" instant ON feature makes it ideal for HID lighting in hard to reach locations.

**Specifications**

<b>Photocell:</b>	Silicone Sensor
<b>Housing:</b>	UV-resistant, high-impact, polypropylene cover with clear UV-stabilized high impact Polycarbonate window. Meets ANSI / cUL color-coded standards
<b>Turn-On:</b>	1 footcandle (fc) nominal
<b>Turn-On/Off Ratio:</b>	1.5:1
<b>Rated Life:</b>	5,000 operations minimum at rated load
<b>Temperature Range:</b>	- 40° to + 70°C - 40° to + 158°F
<b>Dimensions:</b>	3.078" Dia.; 2.219"H
<b>Surge Protection</b>	190 MOV joule rating

**Ordering Information**

Model	Line Voltage	HID Load Rating	Tungsten Load Rating
FP7760-SSS	120 V	1800VA	1000W
FP7772	195-305 V	1800VA	1000W
FP7790B-SSS	105-305 V	1800VA	1000W
FP7794*	315-530 V	1800VA	1000W
FP7790B-RA**	105-305 V	1800VA	1000W

\* Not CUL Listed

\*\* Reverse acting photocontrol - Not CUL Listed

See page 12-15 for LED Controls

**Not recommended for LED installations**

The information in this document is provided for informational use only and is subject to change without notice.

© 2020 by Sunrise Technologies, Inc. All rights reserved.

Doc: FP V082420.7