



FPN7840 Series



FPSI201



FPSI202

FPN7840 GE Astrodome® Replacement Controls

Direct replacement for use in Astrodome-type lighting fixtures.

Specifications

Photocell:	Silicon Sensor
Switch Type:	SPST-NC (single-pole, single-throw, normally closed) electromagnetic relay
Housing:	UV-resistant, high-impact, polypropylene with clear UV-stabilized window
Turn-On:	1 footcandle (fc)
Turn-On/Off ratio:	1.5:1
Rated Life:	5,000 operations minimum at rated load
Temperature Range:	- 40° to + 70°C - 40° to + 158°F
Dimensions:	3.25" Dia.; 2.0" H
Wire Length:	24" cable

Ordering Information

Model	Line Voltage	Load Rating HID Ballast
FPN7841	105-130	1800VA
FPN7842	105-305	1800VA

® Registered trademark of General Electric Company

SI200 Series Screw In Controls

Specifications

Photocell:	Silicon Sensor
Housing:	Polycarbonate
Operating Level:	3 to 10 footcandles (fc)
Temperature Range:	- 40° to + 70°C - 40° to + 158°F
Power Consumption:	0.5Watts
Screw Shell:	Medium base

Ordering Information

Model	Line Voltage	Load Rating
FPSI201	120V	150W incandescent
FPSI202	120V	150W incandescent

Not recommended for LED installations

The information in this document is provided for informational use only and is subject to change without notice.

© 2020 by Sunrise Technologies, Inc. All rights reserved.

Doc: V082420.5